






Each 350mm diameter Solatube system comprises a **Dome & angle kit, a Roof flashing and a Ceiling diffuser**. Extension tubes for systems over 400mm in length and any optional accessories may then be added to each system as required – please see overleaf.



### 350mm Ø Dome & angle kit – one required per system:

|   |  |                       |
|---|--|-----------------------|
|  | <b>Roof dome assembly:</b><br>Polycarbonate roof dome, LITD® dome reflector, Raybender® Technology Fresnel Lens, dome ring, condensation filter & dome/flashing brush seal | Part number<br>121465 |
|   | <b>Top tube assembly</b><br>305mm long 0° to 30° angle adaptor with dome ring  |                       |
|   | <b>Bottom tube assembly</b><br>305mm long 0° to 30° angle adaptor with ceiling ring  |                       |
|   | <b>All fixings &amp; fasteners</b>   |                       |
|   | <b>Installation instructions</b>   |                       |

### 350mm Ø Roof flashing – one required per system:

|   |   |                          |
|---|---|--------------------------|
|    | Flexible aluminium-based universal tile flashing incorporating straight 100mm upstand | Part number<br>230880    |
|   | Slate/plain tile flashing incorporating offset upstand + sealant                      | Part number<br>SABS350BK |
|  | Metal flat roof flashing incorporating 150mm straight upstand + sealant               | Part number<br>200430    |
|  | Wall mounted metal flashing incorporating offset upstand + sealant                    | Part number<br>200660    |

### 350mm Ø Ceiling diffuser – one required per system:

|   |   |                       |
|---|---|-----------------------|
|  | <b>Curved prismatic diffuser</b> – double glazed, curved surface with prisms providing an even spread of light<br><i>NB: The Curved prismatic diffuser is supplied unless otherwise specified</i> | Part number<br>420990 |
|  | <b>Flush frosted diffuser</b> – double glazed, flat surface with 'sandblasted' appearance to provide slightly more focused 'task' light   | Part number<br>420960 |



**OptiView® diffuser** – double glazed, multiple Fresnel lens diffuser providing sky views through each lens

Part number  
420970

## 350mm Ø Extension tubes

The distance from roof to ceiling will determine the number of extension tubes required. Establish the distance from roof to ceiling (x in the picture below) and use the chart to calculate the quantity of extension tubes required. All tubes are 610mm long, made from super reflective (99.7%) Spectralight® Infinity.

|                     |                     |                                |                               |
|---------------------|---------------------|--------------------------------|-------------------------------|
|                     | <b>Distance 'x'</b> | <b>Quantity tubes required</b> | <p>Part number<br/>300320</p> |
|                     | up to 400mm (16")   | 0                              |                               |
|                     | up to 960mm (38")   | 1                              |                               |
|                     | up to 1520mm (60")  | 2                              |                               |
|                     | up to 2080mm (82")  | 3                              |                               |
|                     | up to 2640mm (104") | 4                              |                               |
|                     | up to 3200mm (126") | 5                              |                               |
|                     | up to 3760mm (148") | 6                              |                               |
| up to 4320mm (170") | 7                   |                                |                               |

## 350mm Ø Optional accessories

Solatube optional accessories are designed to complement the Solatube system and integrate neatly into the 350mm diameter Solatube system.

|  |   |                               |
|--|---|-------------------------------|
|  | <p><b>Integral electric light kit</b><br/>The convenience of a switched electric light for night time use – Edison screw fitting, up to 75 watt</p>   | <p>Part number<br/>510120</p> |
|  | <p><b>Electric daylight dimmer kit</b><br/>Fingertip control allows you to choose the amount of daylight allowed through the Solatube – ideal for bedrooms, includes low voltage wall switch &amp; wiring</p> | <p>Part number<br/>570002</p> |
|  | <p><b>Additional 0-90° angle</b><br/>Allows easy installation around obstructions and corners</p>   | <p>Part number<br/>301980</p> |